

## ROMAN BLIND SYSTEM (RBS) INSTALLATION INSTRUCTIONS

FOLLOW THESE INSTRUCTIONS, YOU'LL BE ENJOYING YOUR NEW DRAPERY HARDWARE SOON.



### GETTING STARTED:

Please read through all instructions carefully before you begin installation.

### UNPACK ALL MATERIALS,

Making sure all components are included:

- 1) assembled RBS rail to your specific size
- 2) mounting brackets
- 3) tension pulley

Note all brackets must be securely attached to the mounting surface. If screws do not hit studs you will need to use a different fastener.

### YOU WILL NEED:

- 1) screws
- 2) screw driver
- 3) metal tape measure

**INSTALLING YOUR ROMAN BLIND SYSTEM:** You are now ready to install your blind hardware.

#### WALL MOUNT

**MEASURE:** Rails are pre-cut to your specified size.

**MARK:** Mark the height you would like the top of the blind rail to be installed.

**ATTACH BRACKET:** Attach your brackets to your desired area. Attached screws through holes for a secure mount.

**ATTACH TRACK:** Insert track into bracket by tilting & applying pressure until it "clicks" into place.

**ATTACH TENSION PULLEY:** Attach the tension pulley to the wall on the control/chain side of your RBS System. The chain should be taut.

#### CEILING MOUNT

**MEASURE:** Rails are pre-cut to your specified size.


**ATTACH BRACKET:** Attach bracket to ceiling by first pre-drilling holes for screw diameter when mounting into a ceiling stud. Otherwise, pre-drill and install anchors first before fastening with screws.

**ATTACH TRACK:** Insert track into bracket by tilting & applying pressure until it "clicks" into place.

**ATTACH TENSION PULLEY:** Attach the tension pulley to the wall on the control/chain side of your RBS System. The chain should be taut.

#### ATTACHING FABRIC TO RAIL

Lower all the pull cords attached to the head-rail by pulling on the chain. Be sure cords are releasing, they sometimes require a little guidance by tugging slightly on them. When your fabric is attached this will not be necessary.



After attaching the fabric to the rail, loosen the cord unit screws & adjust the cord position according to the rings on your shade